



Residential Driveway/Apron Brick Paver Specifications

1. **Only brick pavers approved by the Village may be used for residential driveway or apron construction.**
2. Construction shall follow the manufacturer's specifications and installation guide. A copy of the specifications and/or installation guide must be submitted at the time of permit application, and are made a part of the permit. **The aggregate base is required to be a minimum of twelve inches (12") of compacted CA-6.**
3. Brick pavers shall not be installed over the portion of the apron used as a public sidewalk.
4. Brick pavers shall not be installed on wet or frozen subgrade.
5. Grass pavers (or landscaping pavers) are not approved for driveway or apron construction.
6. Any proposed change to existing grade must be approved by the Village prior to the start of any construction.
7. Edge Restraint – Adequate edge restraint shall be provided along the perimeter of all driveways and aprons. The use of paver curbs, concrete curb, edge strip (plastic or metal) or existing structures are approved restraint systems. See edge restraint details.
8. The Village recommends that a sealer be placed on the brick pavers after installation.
9. **Hold Harmless Agreement** – The owner of the property must complete a Hold Harmless Agreement for a Brick Paver Driveway/Apron installation.
10. The Community Development Department must inspect the sidewalk, curb and base before any brick pavers are placed. Please call **(847) 357-4220** at least 24 hours in advance to schedule inspections. Your **permit number** will be required at this time.